


ROTATIONAL MOTION

CONCEPT SUMMARY

KEY CONCEPTS | FORMULAS | RECOGNITION CUES
MISCONCEPTIONS | EXAM TRAPS | QUICK CHECKS



UNDERSTAND
THE PHYSICS



RECOGNIZE
THE PATTERN



SOLVE WITH
CONFIDENCE

SAME PHYSICS.
A HIGHER SCORE.

1. Chapter in One View

Central idea: identify what is rotating, choose the relevant axis, determine what changes, identify the physical cause, and then select the governing relation.

- Describe rotation using angular displacement θ , angular velocity ω and angular acceleration α .
- Connect angular and linear quantities using the distance from the axis.
- Use net torque to explain angular acceleration; use force and torque balance for equilibrium.
- Choose moment of inertia only after identifying both the body and the axis.
- Check net external torque before applying angular-momentum conservation.
- Choose dynamics or energy according to the information given and the quantity asked.
- For rolling, combine translation and rotation using the no-slip constraint.
- For stability, locate the centre of mass relative to the support base.

2. Must-Know Concepts

- Fixed-axis rigid-body rotation: all points share the same angular displacement, angular velocity and angular

NEET PHYSICS ESSENTIALS • ROTATIONAL MOTION

acceleration, but generally have different linear speeds and accelerations.

- Angular displacement θ is measured in radians in the standard angular–linear relations.
- Angular velocity ω describes the rate of change of angular position; angular acceleration α describes the rate of change of angular velocity.
- Tangential acceleration changes speed; radial (centripetal) acceleration changes the direction of velocity.
- Torque depends on force and the perpendicular distance from the axis to the force's line of action.
- Static equilibrium of a rigid body requires both zero net external force and zero net external torque.
- A couple has zero net force but can produce a non-zero torque.
- Moment of inertia measures resistance to angular acceleration about a specified axis; it depends on mass distribution and the chosen axis.
- Angular momentum depends on motion and the chosen reference point/axis. Conservation requires zero net external torque about that point/axis.
- Rotational work is energy transferred by torque through angular displacement; power is the rate of energy transfer.
- Pure rolling combines centre-of-mass translation and rotation. On a stationary surface, $v_{CM} = R\omega$ when rolling without slipping.

- Equilibrium can be stable, unstable or neutral depending on how the system responds to a small displacement.

3. Formula + Meaning

Angular and linear motion

$$s = r\theta$$

Meaning: Arc length corresponding to angular displacement θ .

Use when: A point moves through angle θ at a fixed radius r .

Condition: θ must be in radians.

Do not use blindly when: The radius or axis changes without accounting for the changing geometry.

Exam trap: Do not substitute degrees directly.

$$v = r\omega$$

Meaning: Tangential speed of a point at distance r from the axis.

Use when: Angular speed and the point's perpendicular distance from a fixed axis are known.

Condition: For fixed-axis rotation; r is the distance from the axis.

Do not use blindly when: You need the velocity direction as well as its magnitude.

Exam trap: All points share ω , not the same v .

$$a_t = r\alpha$$

Meaning: Tangential acceleration due to changing angular speed.

NEET PHYSICS ESSENTIALS • ROTATIONAL MOTION

Use when: Angular acceleration is known for fixed-axis rotation.

Condition: Use the point's distance r from the axis.

Do not use blindly when: Only velocity direction changes while speed remains constant.

Exam trap: Tangential acceleration is not radial acceleration.

$$a_r = \frac{v^2}{r} = r\omega^2$$

Meaning: Radial acceleration toward the centre of the circular path.

Use when: A point follows a circular path and its speed or angular speed is known.

Condition: Use the radius of that point's circular path.

Do not use blindly when: The path is not circular or the required quantity is tangential acceleration.

Exam trap: Uniform circular motion has radial acceleration even when $a_t = 0$.

Fixed-axis rotation: same ω , different linear speeds




Figure 1. Fixed-axis rotation: all points share ω , but linear speed depends on radius.

$$\alpha_{avg} = \frac{\Delta\omega}{\Delta t}; \alpha = \frac{d\omega}{dt}$$

Meaning: Average and instantaneous angular acceleration.

Use when: Angular velocity changes over time.

Condition: Use the derivative for instantaneous acceleration.

Do not use blindly when: A constant- α equation is used when α varies.

Exam trap: Check signs against the chosen positive direction.

Constant angular acceleration

$$\omega = \omega_0 + \alpha t;$$

$$\theta - \theta_0 = \omega_0 t + \frac{1}{2} \alpha t^2$$

$$\omega^2 = \omega_0^2 + 2\alpha(\theta - \theta_0)$$

Meaning: Rotational counterparts of constant-acceleration kinematics.

Use when: Angular acceleration is constant and the initial state is known.

Condition: These equations require constant α .

Do not use blindly when: Torque or α varies so that angular acceleration is not constant.

Exam trap: Do not use them merely because the motion is rotational.

Torque and rotational dynamics

$$\tau = rF \sin \phi = Fd_{\perp}$$

Meaning: Turning effect of a force about a chosen point or axis.

Use when: A force acts at a known position and its line of action can be located.

Condition: ϕ is the angle between r and F ; $d_{\perp}$ is the perpendicular distance from the axis to the line of action.

Do not use blindly when: The line of action passes through the axis; torque is then zero.

Exam trap: The distance to the point of application is not necessarily the lever arm.

Recognition tip: use $rF \sin \phi$ when r and the angle are known; use $Fd_{\perp}$ when the perpendicular lever arm is easiest to identify.

Torque geometry and lever arm




Figure 2. Torque is force multiplied by the perpendicular lever arm.

$$\sum \tau = I\alpha$$

Meaning: Net torque produces angular acceleration about a fixed axis.

Use when: The body rotates about a fixed axis and I is calculated about that same axis.

Condition: Use the net torque component about the rotation axis.

Do not use blindly when: The axis is not fixed or a general three-dimensional angular-momentum analysis is required.

Exam trap: Use signed torques consistently; one force's torque is not automatically the net torque.

$$\sum F = 0 \text{ and } \sum \tau = 0$$

Meaning: Conditions for static equilibrium of a rigid body.

Use when: The body remains at rest in an inertial frame.

Condition: Include every external force and its torque about a consistent point.

Do not use blindly when: Only one of the two conditions has been checked.

Exam trap: Zero net force alone does not guarantee rotational equilibrium.

Efficient method: choose the torque point so that unknown forces acting through that point contribute zero torque.

$$\tau_{\text{couple}} = Fd$$

Meaning: Torque of a couple, where d is the perpendicular separation between the two force lines.

Use when: Two equal, opposite, parallel forces act along distinct lines.

Condition: d is the perpendicular distance between their lines of action.

Do not use blindly when: The forces do not form a couple.

Exam trap: A couple can turn a body even though its net force is zero.

Moment of inertia

$$I = \sum m_i r_i^2; I = \int r^2 dm$$

Meaning: Measures how mass is distributed relative to an axis.

Use when: Masses and their perpendicular distances are known, or a continuous distribution is given.

Condition: r is the perpendicular distance from the axis.

Do not use blindly when: The body or axis has not been identified.

Exam trap: Moment of inertia belongs to the body–axis combination.

$$I = Mk^2$$

Meaning: Defines radius of gyration k .

Use when: An equivalent effective distance for the mass distribution is required.

Condition: k refers to the same axis as I .

Do not use blindly when: You assume k must equal the physical radius of the object.

Exam trap: Radius of gyration is an effective distance, not necessarily an actual edge.

$$I = I_{CM} + Md^2$$

Meaning: Parallel-axis theorem.

Use when: The moment about a parallel axis through the centre of mass is known.

Condition: Axes are parallel; d is their perpendicular separation.

Do not use blindly when: The known axis is not through the centre of mass or axes are not parallel.

Exam trap: Use the correct M and axis separation.

$$I_z = I_x + I_y$$

Meaning: Perpendicular-axis theorem for a planar lamina.

Use when: x and y axes lie in the plane and z is perpendicular to it; all pass through the same point.

Condition: The body is a planar lamina.

Do not use blindly when: The object is an arbitrary three-dimensional solid.

Exam trap: Do not apply it to every solid body.

Standard moments of inertia

Body	Axis of Rotation	Moment of Inertia (I)
Thin rod	Centre; axis $\perp$ to rod	$\frac{ML^2}{12}$
Thin rod	One end; axis $\perp$ to rod	$\frac{ML^2}{3}$
Thin ring	Central axis $\perp$ to plane	MR^2
Thin ring	About a diameter	$\frac{MR^2}{2}$
Uniform disc	Central axis $\perp$ to plane	$\frac{MR^2}{2}$
Uniform disc	About a diameter	$\frac{MR^2}{4}$
Solid cylinder	Symmetry axis	$\frac{MR^2}{2}$
Thin hollow cylinder / hoop	Symmetry axis	MR^2
Solid sphere	About a diameter	$\frac{2MR^2}{5}$
Thin spherical shell	About a diameter	$\frac{2MR^2}{3}$

Axis check: before selecting a table value, match both the object's geometry and the specified axis.

Angular momentum, work, energy and power

$$\mathbf{L} = \mathbf{r} \times \mathbf{p} ; [L] = rps \sin \phi$$

Meaning: Angular momentum of a particle about a chosen point.

Use when: Position relative to the reference point and momentum are known.

Condition: ϕ is the angle between $\mathbf{r}$ and $\mathbf{p}$.

Do not use blindly when: The reference point is unspecified.

Exam trap: Angular momentum depends on the chosen reference point.

$$\mathbf{L} = I\omega$$

Meaning: Angular momentum of a rigid body in the standard fixed-axis model.

Use when: Fixed-axis rotation and I about that axis are known.

Condition: Use the actual rotation axis and the applicable rigid-body model.

Do not use blindly when: A general three-dimensional rotation requires more general treatment.

Exam trap: Do not substitute I about a different axis.

$$\tau_{ext,net} = \frac{dL}{dt} ; \Delta L = \int \tau_{ext,net} dt$$

Meaning: Net external torque changes angular momentum; its time integral gives angular-momentum change.

NEET PHYSICS ESSENTIALS • ROTATIONAL MOTION

Use when: Angular-momentum change over a time interval is required.

Condition: Use the same reference point/axis for torque and L .

Do not use blindly when: You assume L is conserved despite a significant net external torque.

Exam trap: Zero net force is not the angular-momentum conservation condition.

$$\tau_{ext,net} = 0 \Rightarrow L = \text{constant}$$

Meaning: Angular momentum is conserved when net external torque about the chosen point/axis is zero or negligible.

Use when: The system and interval have negligible net external torque about that point/axis.

Condition: Check system boundary, reference point and torque during the whole interval.

Do not use blindly when: You have checked only that net external force is zero.

Exam trap: Conservation depends on torque, not force.

$$K_{rot} = \frac{1}{2} I \omega^2$$

Meaning: Kinetic energy associated with rotation about an axis.

Use when: A rigid body rotates with angular speed ω .

Condition: I is about the rotation axis.

Do not use blindly when: Rolling translation is present and total kinetic energy is requested.

Exam trap: For rolling, add translational kinetic energy.

$$W = \int \tau d\theta; \quad W = \tau \Delta\theta \text{ (constant } \tau \text{)}$$

Meaning: Work done by torque through angular displacement.

Use when: Torque acts through a known angular displacement.

Condition: The product $\tau \Delta\theta$ applies when torque is constant.

Do not use blindly when: Torque varies and a single value is used without justification.

Exam trap: Work and torque are different physical quantities.

$$P = \tau\omega$$

Meaning: Instantaneous rotational power for torque and angular velocity about the same axis.

Use when: The rate of rotational energy transfer is required.

Condition: Use the torque component along the rotation axis.

Do not use blindly when: Total work rather than rate is requested.

Exam trap: Power can be negative when torque opposes angular motion.

Rolling motion

$$v_{CM} = R\omega; \quad a_{CM} = R\alpha$$

Meaning: Translation–rotation constraint for pure rolling.

Use when: A circular body rolls without slipping on a stationary surface.

Condition: Use the radius R and compatible signed directions.

Do not use blindly when: The body slips or surface motion has not been accounted for.

Exam trap: This is a kinematic constraint, not a force law.

Pure rolling on a stationary surface




Figure 3. Ideal pure rolling: top point $2v_{CM}$, centre v_{CM} , contact point zero (ground frame).

$$K_{total} = \frac{1}{2} M v_{CM}^2 + \frac{1}{2} I_{CM} \omega^2$$

Meaning: Total kinetic energy of a rolling rigid body.

Use when: The body both translates and rotates about its centre of mass.

Condition: Use I_{CM} for the rotational term in this decomposition.

Do not use blindly when: One component of motion is omitted.

Exam trap: Do not count the same energy twice.

$$a_{CM} = \frac{g \sin \beta}{1 + \frac{I_{CM}}{MR^2}}$$

Meaning: Acceleration down an incline for ideal rolling without slipping.

Use when: A body rolls down a fixed incline under gravity.

Condition: Pure rolling holds and no additional force/torque changes the model.

Do not use blindly when: The body slides or an applied force changes the dynamics.

Exam trap: For the same M and R, larger I_{CM} generally gives smaller acceleration.

$$Mgh = \frac{1}{2}Mv^2 + \frac{1}{2}I_{CM}\left(\frac{v^2}{R^2}\right)$$

Meaning: Gravitational potential energy converted into translational and rotational kinetic energy.

Use when: A rolling body descends through height h and mechanical energy is conserved.

Condition: Pure rolling; no dissipative energy loss; $v = R\omega$.

Do not use blindly when: Slipping or other significant energy transfer occurs.

Exam trap: Use the correct I_{CM} for the body.

Equilibrium describes a state in which the net force and net torque are zero. Stability describes what happens after a small displacement.

NEET PHYSICS ESSENTIALS • ROTATIONAL MOTION

- Stable equilibrium: a small displacement produces a tendency to return to the original position.
- Unstable equilibrium: a small displacement produces a tendency to move farther away.
- Neutral equilibrium: a small displacement leaves the body in a new equilibrium position.
- For support on a base, stability is maintained while the vertical line through the centre of mass falls within the support base.

5. Formula Selection Guide

Situation	Think This Model	Use This
Point at radius r ; angular speed known	Angular-linear link	$v = r\omega$
Angular velocity changes	Rotational kinematics	$\alpha = \Delta\omega/\Delta t$; constant- α equations only if valid
Force and angle are known	Torque geometry	$\tau = rF \sin \phi$
Perpendicular lever arm is known	Torque geometry	$\tau = Fd_{\perp}$
Beam / ladder at rest	Rigid-body equilibrium	$\Sigma F = 0$ and $\Sigma \tau = 0$
Fixed axis and net torque	Rotational dynamics	$\Sigma \tau = I\alpha$
Parallel axis	Parallel-axis theorem	$I = I_{CM} + Md^2$

Situation	Think This Model	Use This
displaced from CM axis		
Planar lamina; perpendicular axes through same point	Perpendicular-axis theorem	$I_z = I_x + I_y$
Mass distribution changes; external torque negligible	Angular-momentum conservation	$I_1 \omega_1 = I_2 \omega_2$ (fixed-axis model)
Torque acts through angular displacement	Rotational work	$W = \int \tau \, d\theta$
Rate of rotational energy transfer	Rotational power	$P = \tau \omega$
Rolling without slipping	Translation + rotation	$v_{CM} = R\omega$
Rolling body descends through height h	Mechanical energy conservation	Mgh $= \frac{1}{2} Mv^2 + \frac{1}{2} I_{CM} \omega^2$
Weight's line reaches support edge	Threshold equilibrium	Take edge as pivot; balance torques at threshold

6. When to Use / When Not to Use

Torque and equilibrium

- Use torque balance when a rigid body is in equilibrium and forces act at different positions.
- Do not infer rotational equilibrium from $\Sigma F = 0$ alone; a couple can have zero net force and non-zero torque.
- Choose a torque point that eliminates unknown forces whose lines of action pass through that point.

Moment of inertia

- Use a standard value only after matching the body, axis and geometry.
- Use the parallel-axis theorem only for parallel axes when the known axis passes through the centre of mass.
- Use the perpendicular-axis theorem only for a planar lamina, with all three axes through the same point.

Selection rule: Always match the object's shape and the stated axis before choosing a formula. M = mass, L = length, R = radius.

Body	Axis of Rotation	Moment of Inertia (I)
Thin rod	Through centre; $\perp$ to rod	$I = \frac{ML^2}{12}$
Thin rod	Through one end; $\perp$ to rod	$I = \frac{ML^2}{3}$

Body	Axis of Rotation	Moment of Inertia (I)
Thin ring / hoop	Central axis $\perp$ to its plane	$I = MR^2$
Thin ring / hoop	About a diameter	$I = \frac{MR^2}{2}$
Uniform disc	Central axis $\perp$ to its plane	$I = \frac{MR^2}{2}$
Uniform disc	About a diameter	$I = \frac{MR^2}{4}$
Solid cylinder	Symmetry axis	$I = \frac{MR^2}{2}$
Thin hollow cylinder / hoop	Symmetry axis	$I = MR^2$
Thick-walled hollow cylinder	Symmetry axis; inner radius R_1 , outer radius R_2	$I = \frac{M(R_1^2 + R_2^2)}{2}$
Solid sphere	About a diameter	$I = \frac{2MR^2}{5}$
Thin spherical shell	About a diameter	$I = \frac{2MR^2}{3}$

Important reminders

- Moment of inertia depends on the chosen axis, not only on the object's shape.
- Parallel-axis theorem: $I = I_{CM} + Md^2$, where d is the perpendicular distance between parallel axes and the known axis passes through the centre of mass.
- For a planar lamina, perpendicular-axis theorem: $I_z = I_x + I_y$, with x and y in the plane and z perpendicular to it; all axes pass through the same point.
- Use the listed formulas for the idealized uniform bodies and axes stated in the table.

Angular momentum

- Conserve angular momentum only when net external torque about the selected point/axis is zero or negligible over the interval.
- For a collision, choose the system and reference point first, then check external impulsive torque.

Rolling and friction

- Use $v_{CM} = R\omega$ only for pure rolling without slipping, accounting for any motion of the surface.
- Static friction adjusts to the value required by the motion, up to its limiting magnitude $f_{s,max} = \mu_s N$; it is not always equal to $\mu_s N$.
- The instantaneous contact point is useful for instantaneous velocity relative to a stationary surface. Do not automatically use it as the pivot for every torque or energy calculation.

7. Common Misconceptions

- Wrong idea: “Every point on a rotating body has the same speed.” → Correct: Angular velocity is common in fixed-axis rigid rotation, but linear speed depends on distance from the axis.
- Wrong idea: “Zero net force means no rotation.” → Correct: A couple can have zero net force and non-zero torque.
- Wrong idea: “Moment of inertia belongs only to the object.” → Correct: It depends on the axis as well as mass distribution.
- Wrong idea: “Zero external force guarantees angular-momentum conservation.” → Correct: Check net external torque about the chosen point or axis.
- Wrong idea: “Static friction always equals $\mu_s N$.” → Correct: $\mu_s N$ is the limiting magnitude; actual static friction adjusts as required within the limit.
- Wrong idea: “The contact point of a rolling wheel is permanently at rest.” → Correct: The material point in contact changes continuously; the instantaneous contact point has zero ground-frame velocity in ideal pure rolling.

8. Exam Traps

- Using point-to-force distance instead of the perpendicular lever arm.
- Mixing clockwise and anticlockwise torque signs.
- Choosing the wrong moment of inertia because the axis differs from the table's axis.

- Using constant-angular-acceleration equations when α is not constant.
- Applying angular-momentum conservation without checking net external torque.
- Using rotational kinetic energy alone when a rolling body's total kinetic energy is required.
- Assuming static friction always equals $\mu_s N$.
- Using $v = R\omega$ when slipping occurs.
- Confusing instantaneous contact-point velocity with centre-of-mass velocity.

9. See This → Think This

- Same ω at different radii → Compare linear speeds using $v = r\omega$.
- Force applied at an angle → Draw its line of action and find the perpendicular lever arm.
- Beam or ladder at rest → Draw a free-body diagram; use force balance and torque balance.
- Net force zero but body tends to turn → Check for a couple or non-zero net torque.
- Shape and axis given → Select I only after matching both.
- Axis shifted parallel to a centre-of-mass axis → Check the parallel-axis theorem.
- Planar lamina and perpendicular in-plane axes → Check the perpendicular-axis theorem.
- Person moves inward on a rotating platform → If external torque is negligible, I decreases and ω increases.

- Collision produces rotation → Choose the point/axis and check external impulsive torque.
- Torque and angular displacement given → Consider the work–energy route.
- Rolling body descends through a known height → Consider conservation of mechanical energy.
- Small displacement from equilibrium → Ask whether the system returns, moves farther away, or remains in its new position.

10. Quick Checks

- Q: Do all points of a fixed-axis rigid body have the same angular velocity? → Yes.
- Q: What determines the linear speed of a point? → $v = r\omega$.
- Q: When is torque of a force zero about a pivot? → When its line of action passes through the pivot.
- Q: What two conditions are needed for static rigid-body equilibrium? → $\Sigma F = 0$ and $\Sigma \tau = 0$.
- Q: What must be identified before selecting a moment-of-inertia formula? → The body and the axis.
- Q: What condition permits angular-momentum conservation? → Zero or negligible net external torque about the chosen point/axis.
- Q: What is the pure-rolling constraint on a stationary surface? → $v_{CM} = R\omega$.
- Q: What terms appear in the kinetic energy of a rolling body? → Translational and rotational kinetic energy.

- Q: Is static friction always $\mu_s N$? $\rightarrow$ No; that is the limiting magnitude.

11. Mini Exam Reasoning

Clue: A force acts at an angle on a rod pivoted at one end. $\rightarrow$

Situation: turning effect about the pivot. $\rightarrow$ Model: torque geometry. $\rightarrow$ Relation: $\tau = rF \sin\phi$ or $Fd_{\perp}$. $\rightarrow$ Check: ϕ is between r and F ; $d_{\perp}$ is perpendicular to the line of action.

Clue: A person moves closer to the axis of a rotating platform. $\rightarrow$

Situation: mass distribution changes. $\rightarrow$ Model: angular-momentum conservation if external torque is negligible. $\rightarrow$

Relation: $I_1\omega_1 = I_2\omega_2$. $\rightarrow$ Check: if I decreases, ω increases when L is conserved.

Clue: A solid sphere rolls down a height h without slipping. $\rightarrow$

Situation: gravitational energy becomes translational and rotational kinetic energy. $\rightarrow$ Model: mechanical energy conservation. $\rightarrow$ Relation: $Mgh = \frac{1}{2}Mv^2 + \frac{1}{2}ICMv^2/R^2$. $\rightarrow$ Check: use the correct ICM and $v = R\omega$.

Clue: A ladder rests against a wall. $\rightarrow$ Situation: static

equilibrium. $\rightarrow$ Model: free-body diagram and balance laws. $\rightarrow$

Relations: $\Sigma F_x = 0$, $\Sigma F_y = 0$, $\Sigma \tau = 0$. $\rightarrow$ Check: choose a torque point that removes as many unknown support forces as possible.

12. One-Minute Recall

- Rotation state $\rightarrow \theta, \omega, \alpha$.
- Angular-linear link $\rightarrow s = r\theta$; $v = r\omega$; $a_t = r\alpha$; $a_r = r\omega^2$.
- Constant $\alpha \rightarrow$ rotational kinematics equations.

NEET PHYSICS ESSENTIALS • ROTATIONAL MOTION

- Torque $\rightarrow$ force $\times$ perpendicular lever arm.
- Fixed-axis dynamics $\rightarrow \Sigma \tau = I\alpha$.
- Static equilibrium $\rightarrow \Sigma F = 0$ and $\Sigma \tau = 0$.
- Moment of inertia $\rightarrow$ body + axis; mass farther from axis contributes more.
- Parallel axis $\rightarrow I = I_{CM} + Md^2$; planar lamina $\rightarrow I_z = I_x + I_y$ when conditions fit.
- Angular momentum $\rightarrow L = r \times p$; fixed-axis form $L = I\omega$.
- Conservation $\rightarrow$ check net external torque, not merely net force.
- Rotational energy $\rightarrow K_{rot} = \frac{1}{2}I\omega^2$; work $W = \int \tau d\theta$; power $P = \tau\omega$.
- Pure rolling $\rightarrow v_{CM} = R\omega$; total kinetic energy has translation and rotation.
- Static friction adjusts up to $\mu_s N$; it is not always at its limiting value.
- Stability $\rightarrow$ stable returns; unstable moves away; neutral remains in a new equilibrium.

Want to Go Deeper?

This website concept summary is designed for fast revision and formula selection. The complete NEET Physics Essentials Concept Book can provide fuller concept development, step-by-step derivations, detailed diagrams, microquestions, solved examples and integrated exam reasoning.

COMPLETE CONCEPT BOOK

Website: www.pickprep.com

WhatsApp: +919737240300

Email: pickprep03@gmail.com

Understand the Physics → Recognize the Pattern → Solve with
Confidence



PickPrep